Systems Operating Seasonally



Alaska Department of Environmental Conservation

Revised Total Coliform Rule-Sample Siting Plan for Seasonal Systems

All public water systems (PWS) are required to have an approved sample siting plan. These plans are required to be updated when changes occur that could alter the number of samples collected or the sample locations. *Examples:* population increase or decrease, water line extensions, changes in monitoring frequency, etc.

I. General Information						
PWS Name: PWSID #:						
PWS Address:						
Contact Name:				Phoi	ne #:	
E-mail: Fax #:					Fax #:	
Water System Type: No	on-Transient Non-Community		Transien	t Non-	Community	
Population Served (# of):	Residents	Non-Transient Transient Total Pop				Total Pop
Number of Service Connec	tions:					
Source Types:	Ground Water		Pu	rchase	d Ground Water	
(Check all that apply)	Surface Water		Pu	rchase	d Surface Water or	GWUDISW*
	GWUDISW*	Filtration Avoidance System (Surface Water)				
*Ground Water Under Direct Infl	uence of Surface Water					
Dates of Operation:	to					
Is your entire system press	surized year-round?	Yes	No			
* If yes, you are not require	ed to complete start-up procedur	es (unless	otherwise dire	ected b	y the DEC).	
Number of Routine Sample	es Required:	per	Month	(Quarter	
	duced) Monitoring, enter the rable* in each quarter you are					
	ater system are typically at the beginning le/highest water demand. As a reminder					

Guidelines for Sample Site Selection

- * Identify total coliform sample locations that adequately represent the entire distribution system(s)
- * Swivel taps, automatic/motion-sensing faucets, and water treatment devices should be avoided
- * Do NOT collect samples from outside taps or hoses
- * Routine sample sites should be accessible for routine and repeat testing
- * Three Repeat samples are required following each total coliform positive routine sample (Systems with wells must also collect a raw source water sample from each active well). Repeat sampling sites should be selected as follows:
 - * One must be collected from the original routine site that tested total coliform positive
 - * One must be collected from within five service connections upstream
 - * One must be collected from within five service connections downstream
- * For systems on quarterly monitoring, you will be required to collect 3 samples the month following a total coliform positive sample. Since the sample site selection will depend on the specific circumstances surrounding the positive sample(s) these sample sites do not need to be included in this plan
- * Ground water source samples must be taken from raw water sample taps

Please return this form to your DEC Drinking Water Program Office.

A copy of this completed sample siting plan must be maintained on file at the PWS.

Anchorage DEC Office
555 Cordova Street
Anchorage, AK 99501
Fax: 269-7650
DEC.DWData.Anchorage@alaska.gov

Fairbanks DEC Office
610 University Ave.
Fairbanks, AK 99709
Fax: 451-2188
DEC.DWData.fairbanks@alaska.gov

43335 K-Beach Road, Suite 11 Soldotna, AK 99669 Fax: 262-2294 dec.dwdata.soldotna@alaska.gov

Soldotna DEC Office

Wasilla DEC Office 1700 E. Bogard Road Building B, Suite 103 Wasilla, AK 99654 Fax: 376-2382

DEC.DWData.wasilla@alaska.gov

Systems Operating Seasonally

II. Sampling Information

A. Routine Sample Rotation Schedule: If you are on Quarterly (reduced) monitoring, enter the month or months your system is most vulnerable* in each quarter you are operating.

system is most varietable. In each quarter you are operating.												
Pouting Cample Site	1st Quarter		2nd Quarter		3rd Quarter			4th Quarter				
Routine Sample Site		Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1.												
2.												
3.												
4.												
5.												

^{*}The most vulnerable times for a water system are typically at the beginning of the season (if your system is not pressurized year round) and during the times when you are serving the most people/highest water demand.

B. Routine and Repeat Sample Locations

Routine Sample Sites	Repeat Sample Sites
Location/Address	Location/Address
1.	1-1
	Original sample site
	1-2
	Upstream
	1-3
	Downstream
2.	2-1
	Original sample site
	2-2
	Upstream
	2-3
	Downstream
3.	3-1
	Original sample site
	3-2
	Upstream
	3-3
	Downstream
4.	4-1
	Original sample site
	4-2
	Upstream
	4-3
	Downstream
5.	5-1
	Original sample site
	5-2
	Upstream
	5-3
	Downstream

C. Reasons for Choosing Routine Sample Locations

[1.	
2.	
3.	
4.	
5.	

PWSID#:

_
>
_
=
O
_
0
M
(O
യ
Seasonal
V)
b 6
O.
.=
io
യ
Ŏ
Operating
Ō
10
9
stems
(1)
- 7.5
- U

Comments:

State Reviewer Signature:

		PWSID#:			
		urce Water Monitoring ow, you are required to perform source water monitoring, from each active well under the			
		tine total coliform positive sample. This sampling is in addition to the repeat sampling ce sample site information in the table below. If you need more space, attach additional			
Do you provide DEC-appr	oved 4-log tre	atment of viruses for all your groundwater sources?			
Yes	No	N/A- We do not have any wells or all of our water is treated as SW or GWUDISW (There are no wells in the distribution system that bypass surface water treatment.)			
	G	roundwater Rule Triggered Source Water Monitoring			
Source ID/Nar	ne	Description of location of raw water sample tap			
DEC Area Office:		Date Received: / /			
Was a dual purpose sar	nple approve	d? Yes No Date discussed with Supervisor: / /			
NOTE: The only systems elig serve a single building with		dual prupose sample are Groundwater systems, serving 1,000 or fewer people, that only have 1 well, and ole taps.			

No

Sample Siting Plan deemed complete and satisfactory? Yes