

## ANALYTICAL METHOD FOR WHITE PHOSPHORUS IN WATER

Marianne E. Walsh  
CRREL

White phosphorus ( $P_4$ ) is a toxic, synthetic substance that has been used in poisons, smoke screens, matches and fireworks and as a raw material to produce phosphoric acid (Parkes 1951). Environmental contamination with  $P_4$  has occurred at facilities that either produce or use  $P_4$  (Jangaard 1972, Pearson et al. 1976) and areas where  $P_4$  munitions have been used (Racine et al. 1992, 1993). While thermodynamically unstable in aqueous solutions (Pourbaix 1966),  $P_4$  residues persist in aquatic environments and have caused massive mortality of fish (Jangaard 1972) and waterfowl (Racine et al. 1992).

Various water quality criteria for the protection of aquatic organisms have been calculated; they range from 0.01 (Davidson et al. 1987) to 0.04  $\mu\text{g}/\text{L}$  (Bentley et al. 1978). For the protection of human health, the Environmental Protection Agency has issued a lifetime health advisory (HA) of 0.1  $\mu\text{g}/\text{L}$ ; because of the extreme toxicity of  $P_4$  following ingestion, HAs for one-day, ten-day and longer-term exposures are not recommended (Gordon et al. 1990).

$P_4$ -contaminated water may contain suspended (colloidal) and dissolved  $P_4$  (Dacre and Rosenblatt 1974). Larger particles (200–400  $\mu\text{m}$ ) may also be suspended (Peer 1972). While the aqueous solubility of  $P_4$  is approximately 3  $\text{mg}/\text{L}$  (Stich 1953), aqueous suspensions containing 200  $\text{mg}/\text{L}$  may be produced by dispersion of molten  $P_4$  (Bullock and Newlands 1969).

A specific analytical method for the determination of  $P_4$  in water was developed in conjunction with studies of the severe adverse environmental impact of a release of effluent from a  $P_4$  production facility in Newfoundland, Canada (Addison and Ackman 1970). This method involved the extraction of  $P_4$  from water by a few minutes of vigorous shaking with an organic solvent, either benzene or isooctane. The ratio of water to solvent was 2:1 v/v.  $P_4$  in the extract was then determined by packed-column gas chromatography with a flame photometric detector. The minimum detectable concentration for this method was estimated to be 0.1  $\mu\text{g}/\text{L}$  using a 5- $\mu\text{L}$  injection with a precision of  $\pm 100\%$  at this concentration. Concentration of the extract by blowdown under an inert gas

increased the sensitivity of the method but further reduced the analytical precision.

Environmental assessments at Pine Bluff Arsenal, Arkansas, the site where  $P_4$  munitions are produced, required an analytical method capable of detecting  $0.01 \mu\text{g/L}$ . Lai and Rosenblatt (1977) developed a method sensitive enough to meet this criterion that was based on solvent extraction with benzene followed by neutron activation analysis. The authors reported poor extraction efficiency if the ratio of water to benzene was greater than 10:1. Preconcentration of the extract by solvent evaporation under an argon atmosphere at room temperature was unsuccessful, since  $P_4$  was lost with the solvent, presumably by volatilization.

While the neutron activation method proved to be sufficiently sensitive, the required instrumentation is not available in most analytical laboratories. The objective of this work was to develop an analytical method capable of meeting water quality criteria for the protection of aquatic organisms that utilizes standard analytical instrumentation. The development focused on a preconcentration step suitable for a volatile, air-sensitive chemical. A nonevaporative preconcentration step, similar to that reported by Jenkins and Miyares (1991), is used that takes advantage of the favorable partitioning of  $P_4$  between organic and aqueous phases [ $K_{ow} = 1200$  (Spangord et al. 1985)] and the relatively high solubility of diethyl ether in water (6.9% w/w at  $20^\circ\text{C}$ ).  $P_4$  is extracted from water using diethyl ether (10:1 water:solvent ratio). The ether phase is collected, then reduced in volume by shaking with reagent-grade water. By using the appropriate volume of water, excess ether is dissolved away, resulting in a preconcentration factor of 1000, while heat is avoided and loss of  $P_4$  by volatilization minimized.  $P_4$  is then determined by capillary gas chromatography utilizing a nitrogen-phosphorus detector.

## MATERIALS AND METHODS

An analytical standard for  $P_4$  was obtained from Aldrich Chemical Co. (Milwaukee, WI). The  $P_4$  was supplied as a 5-g stick with a white coating under water. Pieces (100–300 mg) from the stick were obtained by placing the stick in degassed water in a nitrogen-purged glove bag and cutting it with a razor blade. Care was taken to ensure that the surfaces of each piece of  $P_4$  were freshly cut,

lustrous in appearance and showed no evidence of a white coating. These pieces were used to prepare solutions as described below.

A stock solution for calibration standards was prepared under nitrogen by dissolving 250 mg of  $P_4$  in 0.50 L of isooctane (Aldrich Chemical Co.). Standards over the range 3.5 to 70  $\mu\text{g/L}$  were prepared by diluting the stock solution with isooctane or diethyl ether.

Aqueous solutions of  $P_4$  were prepared by placing pieces of  $P_4$  into an amber jug containing 4 L of Type I water (MilliQ, Millipore) with no headspace and agitating the jug for over 60 days.

Field samples were obtained from Eagle River Flats in amber glass bottles filled so that there was no headspace. Samples were maintained at 4°C until extracted. Samples were extracted and analyzed within five days after collection.

Two methods were used to extract water samples. The first method was based on previous work (Addison and Ackman 1970). A 30-mL subsample was shaken for 5 minutes with 3.00 mL of isooctane in a 40-mL amber vial. Then the isooctane layer was taken for analysis. For the second method a 500-mL aliquot of water was extracted with 50 mL of diethyl ether by shaking in a 500-mL separatory funnel for 5 minutes. After phase separation, all of the ether layer was collected. The volume of the ether layer recovered varied, depending on the temperature of the sample and the ionic strength of the samples; it generally ranged from 3 to 10 mL. The volume of the ether layer was further reduced to approximately 0.5 mL by adding the ether extract to approximately 50 mL of reagent-grade water in a 125-mL separatory funnel and shaking for 1 minute. After phase separation the ether layer was collected and the exact volume was measured. The  $P_4$  concentration in the extract was then determined by gas chromatography.

$P_4$  was determined by injecting a 1.0- $\mu\text{L}$  aliquot of the isooctane or ether extract on-column into an SRI Model 8610 gas chromatograph equipped with a nitrogen-phosphorus detector. The methylsilicone fused-silica column (J and W DB-1, 0.53-mm-I.D., 15-m, 3.0- $\mu\text{m}$  film thickness) was maintained at 80°C. The carrier gas was nitrogen set at 30 mL/min. Under these conditions,  $P_4$  eluted at two minutes.

## RESULTS AND DISCUSSION

An initial test of this procedure was conducted using an aqueous test solution prepared by sequential dilution of the aqueous P<sub>4</sub> stock. The objective was to determine if sufficient preconcentration could be obtained by extraction of P<sub>4</sub> from 500 mL of water with 50 mL of ether, followed by nonevaporative reduction of the volume of the ether extract to 0.5 mL by dissolution in reagent-grade water. The concentration of the aqueous stock solution, as determined by isooctane extraction followed by gas chromatography, was 650 µg/L. An aqueous test solution was prepared by sequential dilution of the stock so that the estimated concentration of the test solution was 0.016 µg/L. Three 500-mL aliquots were processed according to the method outlined above. The P<sub>4</sub> concentrations found were 0.007, 0.016 and 0.019 µg/L. The total processing time, including extraction and analysis, was about 30 minutes per sample. Based on these results, this technique appeared to provide sufficient preconcentration to meet water quality criteria, and further tests were performed to determine the method detection limit, recovery and performance with field samples.

A method detection limit (MDL) was determined by extracting seven replicate 500-mL water samples with P<sub>4</sub> concentrations in the range of 0.01 µg/L (Federal Register 1984). To prepare a bulk aqueous sample, approximately 3 mL of the P<sub>4</sub> aqueous stock solution was added to a 1-L amber bottle containing reagent-grade water. The bottle was filled with reagent-grade water, then inverted several times over a 10-minute period. An aliquot was taken and extracted with isooctane, and the P<sub>4</sub> was determined. The concentration of P<sub>4</sub> was 2 µg/L. A further 1:100 dilution was made by transferring 40 mL of the 2-µg/L aqueous solution into a 4-L amber glass jug containing reagent-grade water, then filling the jug with reagent-grade water. This bulk aqueous sample was mixed by inverting the jug for 10 minutes; then seven 500-mL aliquots were extracted with 50 mL of diethyl ether. The volume of ether recovered ranged from 3 to 4 mL. This volume was reduced to approximately 0.5 mL by mixing it with 20–30 mL of reagent-grade water in a 125-mL separatory funnel. The actual volume recovered was measured in a 10-mL graduated cylinder and was used to calculate the concentration.

P<sub>4</sub> was easily detectable in each of the seven samples, with found concentrations ranging from 0.022 to 0.031 µg/L (Table A-3-1). An MDL of 0.011 µg/L was obtained. To estimate recovery, seven water samples (500 mL) were

**Table A-3-1. P<sub>4</sub> concentrations found in seven replicate 500-mL water samples following extraction with diethyl ether.**

	<u>P<sub>4</sub> Conc. (µg/L)</u>
	0.027
	0.029
	0.022
	0.030
	0.023
	0.031
	<u>0.030</u>
mean =	0.027
std. dev. =	0.0036
t (n-1, α=0.99) =	3.143
MDL =	0.011

fortified with 0.5 mL of a P<sub>4</sub> spike solution prepared in ether to yield an aqueous P<sub>4</sub> concentration of 0.07 µg/L. The mean recovery was 107±12%.

To test how the method would perform with actual samples, twenty-one 1-L water samples were collected from a field site contaminated with residues from P<sub>4</sub> munitions (Racine et al. 1993). A sediment sample was also collected at each location. The sediment samples were analyzed for P<sub>4</sub> using the gas chromatographic procedure described by Walsh and Taylor (1993). For each water sample, two subsamples were extracted, one using the isooctane extraction procedure of Addison and Ackman (1970) and one using the diethyl ether procedure described above. Of these 21 samples, no P<sub>4</sub> was detected using the isooctane extraction. However, P<sub>4</sub> was detectable in six samples using the ether extraction/nonevaporative preconcentration procedure. Concentrations ranged from 0.011 to 0.069 µg/L. These six positive water samples were collected from the same locations as the only six sediment samples where P<sub>4</sub> was detected. However, the concentrations of P<sub>4</sub> found in the water were not correlated with the concentrations found in the sediment (Table A-3-2). All locations were in open water ponded areas where significant dilution with uncontaminated water is possible.

The volume of ether recovered varied with the conductivity and temperature of the sample. Based on the solubility of ether in water (6.89% w/w at 20°C and 6.05% at 25°C) and the density of ether (0.7133 g/mL at 20°C and 0.7076 g/mL at 25°C), the volume of ether recoverable when 50 mL of ether are mixed with 500 mL of pure water with temperatures between 22° and 25°C will range from 1 to 5

**Table A-3-2. P<sub>4</sub> concentrations found in water and sediment samples collected from a field site contaminated with residues of P<sub>4</sub> munitions.**

<i>Sample</i>	<i>P<sub>4</sub> conc. in water (μg/L)</i>	<i>P<sub>4</sub> conc. in sediment (μg/g)</i>
1	0.011	0.079
2	0.013	0.43
3	0.016	1.6
4	0.020	1700
5	0.043	0.0143
6	0.069	0.205

mL (Windholz et al. 1976). As the aqueous concentration of electrolytes increases, the volume of recoverable ether will increase due to salting-out of the organic phase (James 1986). The conductivity of the field samples ranged from 0.07 to 51 mmhos/cm, with a mean of  $18.2 \pm 17.4$  mmhos/cm. The volume of ether recovered ranged from 0.4 to 17 mL, with a mean of  $6.7 \pm 5.0$  mL. The lowest volume recovered corresponded to a sample that had not warmed to room temperature prior to extraction; the conductivity of the sample was 3.9 mmhos/cm. Volumes greater than 10 mL were recovered from samples with conductivities exceeding 30 mmhos/cm. In all cases the volume was easily reduced to approximately 0.5 mL by mixing the recovered ether with reagent-grade water, the volume of which was adjusted according to the volume of ether added. An example calculation is as follows for the case where 5.0 mL of ether is recovered from a sample at 25°C:

1. Volume of excess ether = 5.0 mL - 0.5 mL = 4.5 mL
2. Mass of excess ether = 4.5 mL  $\times$  0.7076 g/mL = 3.18 g
3. Mass of aqueous solution saturated with 3.18 g ether = 3.18 g / 0.0605 = 52.6 g
4. Mass of water in aqueous solution saturated with 3.18 g ether = 52.6 g - 3.18 g = 49.4 g
5. Volume of water required to dissolve 4.5 mL ether at 25°C = 49.4 g / 0.997 g/ml = 49.5 mL

Calculations need only be made once, if the results are entered into a table for future reference.

Further work is being performed to evaluate the pre-extraction holding times for P<sub>4</sub> in aqueous samples. In the meantime the procedure as outlined here provides a technique for measuring P<sub>4</sub> at the current water quality criteria. The nonevaporative/preconcentration method described here may be suitable for

other volatile or thermally degradable nonpolar chemicals since it does not rely on solvent evaporation.

## ACKNOWLEDGMENTS

The author gratefully acknowledges the funding for this work, which was provided by the U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS (U.S.A.), Ann Strong, Project Monitor; technical reviews provided by Dr. Thomas F. Jenkins and Philip G. Thorne; and field samples provided by Carl Bouwkamp of the U.S. Army Environmental Hygiene Agency. This publication reflects the personal views of the authors and does not suggest or reflect the policy, practices, programs or doctrine of the U.S. Army or the Government of the United States.

## REFERENCES

- Addison, R.F. and R.G. Ackman** (1970) Direct determination of elemental phosphorus by liquid-gas chromatography. *J. of Chromatog.*, **47**: 217-222
- Bentley, R.E., J.W. Dean, T.A. Hollester, G.S. Leblanc, B.H. Sauter and W.G. Wilson** (1978) Laboratory evaluation of the toxicity of elemental phosphorus (P<sub>4</sub>) to aquatic organisms. ADA061785, U.S. Army Medical Research and Development Command, Fort Detrick, Frederick, MD.
- Bullock, E. and M.J. Newlands** (1969) Decomposition of phosphorus in water. In *Effects of Elemental Phosphorus on Marine Life: Collected Papers Resulting from the 1969 Pollution Crisis, Placentia Bay, Newfoundland* (P.M. Jangaard, Ed.). Circular No. 2. Fisheries Research Board of Canada, Halifax, Nova Scotia, p. 55-56.
- Dacre, J.C. and D.H. Rosenblatt** (1974) Mammalian toxicology and toxicity to aquatic organisms of four important types of waterborne munitions pollutants - An extensive literature evaluation. Technical Report 7403. AD778725, U.S. Army Medical Bioengineering Research and Development Laboratory, Aberdeen Proving Ground, MD.
- Davidson, K.A., P.S. Hovatter and C.F. Sigmon** (1987) Water quality criteria for white phosphorus. ORNL-6336, Oak Ridge National Laboratory
- Federal Register** (1984) Definition and procedure for the determination of the method detection limit. Part 136, Appendix B, Code of Federal Regulations.

- Gordon, L., W.R. Hartley and W.C. Roberts** (1990) Health advisory on white phosphorus. U.S. Environmental Protection Agency.
- James, K.C.** (1986) *Solubility and Related Properties*. Marcel Dekker, Inc., New York
- Jangaard, P.M.** (1972) Effects of elemental phosphorus on marine life. Atlantic Regional Office, Research and Development, Fisheries Research Board of Canada, Halifax, Nova Scotia, p. 313.
- Jenkins, T.F. and P.H. Miyares** (1991) Nonevaporative preconcentration technique for volatile and semi-volatile solutes in certain polar solvents. *Anal. Chem.*, **63**: 1341-1343.
- Lai, M.G. and D.H. Rosenblatt** (1977) Determination of ultramicro quantities of elemental phosphorus in water by neutron activation analysis. NSWC/WOL/TR-77-49. ADA091773, Naval Surface Weapons Center, White Oak, Silver Spring, MD.
- Parkes, G.D.** (1951) Phosphorus and the remaining elements of Group V. In *Mellor's Modern Inorganic Chemistry*, Longmans, Green and Co, London, p. 751-773.
- Pearson, J.G., E.S. Bender, D.H. Taormina, D.L. Manuel, P.F. Robinson and A.E. Asaki** (1976) Effects of elemental phosphorus on the biota of yellow lake, Pine Bluff Arsenal, Arkansas, March 1974 - January 1975. Technical Report EO-TR-76077, Edgewood Arsenal.
- Peer, D.L.** (1972) Observations on mortalities of benthic organisms and contamination of the bottom of Long Harbour, Placentia Bay, Newfoundland, with elemental phosphorus. In *Effects of Elemental Phosphorus on Marine Life: Collected Papers Resulting from the 1969 Pollution Crisis, Placentia Bay, Newfoundland* (P.M. Jangaard, Ed.). Circular No. 2. Fisheries Research Board of Canada, Halifax, Nova Scotia, p. 181-186.
- Pourbaix, M.** (1966) *Atlas of Electrochemical Equilibria in Aqueous Solutions*. Pergamon Press, Oxford.
- Racine, C.H., M.E. Walsh, C.M. Collins, S.T. Taylor, B.D. Roebuck, L. Reitsma and B. Steele** (1993) Remedial investigation report for white phosphorus contamination in an Alaskan salt marsh. CRREL Report No. 93-17, U.S. Army Cold Regions Research and Engineering Laboratory, Hanover, New Hampshire.
- Racine, C.H., M.E. Walsh, B.D. Roebuck, C.M. Collins, D. Calkins, L. Reitsma, P. Buchli and G. Goldfarb** (1992) White phosphorus poisoning of waterfowl in an Alaskan salt marsh. *J. Wildlife Diseases*, **28**: 669-673.



- Spanggord, R.J., R. Renwick, T.W. Chou, R. Wilson, R.T. Podoll, T. Mill, R. Parnas, R. Platz and D. Roberts (1985) Environmental fate of white phosphorus/felt and red phosphorus/butyl rubber military screening smokes. ADA176922, U.S. Army Medical Research and Development Command.
- Stich, C. (1953) Solubility of phosphorus. *Pharmazie*, 8: 202.
- Walsh, M.E. and S.T. Taylor (1993) Analytical method for white phosphorus in munitions-contaminated sediments. *Anal. Chim. Acta*, 282: 55–61.
- Windholz, M., S. Budavari, L.Y. Stroumstos and M.N. Fertig (1976) *The Merck Index*. Merck and Co., Inc., Rahway, NJ.