

Earth and Environmental Technologies

Hart Crowser, Inc. 2550 Denali Street, Suite 705 Anchorage, Alaska 99503-2737 Fax 907.276.2104 Tel 907.276.7475

Dept. of Environmental Conservation

inderground Storage Tanks - FAP

A-8397-06

December 26, 1996

Mr. Jon Clark Municipality of Anchorage Department of Property and Facility Management 3640 East Tudor Road Anchorage, Alaska 99519-6650

Re:

Remediation System Operation and Monitoring

August 7 through November 20, 1996 Anchorage Fire Department Station No. 4

Dear Mr. Clark:

This letter report presents the hydrocarbon recovery activities and results of groundwater sampling at the Municipality of Anchorage (MOA) Fire Department Station No. 4 (AFD-4) for the period of August 7 through November 20, 1996. AFD-4 is located at 4350 MacInnes Road in Anchorage, Alaska.

In January 1995, two recovery wells were installed at the site to collect floating hydrocarbons (Figure 1) using Petro-trap passive hydrocarbon pumps. Work was conducted in accordance with the Corrective Action Plan for this site dated October 19, 1994. This plan was approved by the Alaska Department of Environmental Conservation in a meeting with the MOA - Department of Property and Facility Management and Hart Crowser on January 13, 1995.

WORK PERFORMED BY HART CROWSER

Product thickness measurements were taken in monitoring well MW-1, and groundwater elevation measurements were taken in monitoring wells MW-2 through MW-4, on November 20. 1996 (Appendix A - Field Methods). Monitoring wells MW-2, MW-3, and MW-4 were then purged and sampled. Samples were submitted to North Creek Analytical (NCA) laboratory for analyses of benzene, toluene, ethylbenzene, and xylenes (BTEX; EPA Method 8020) and dieselrange organics (DRO; EPA Method 8100M).

WATER TABLE CONDITIONS

Groundwater elevations declined 0.04 feet in MW-1, 0.48 feet in MW-2, 0.05 feet in MW-3, and 0.26 feet in MW-4 over the monitoring period (Figure 2). The inferred groundwater contours for this site, for November 20, 1996, are presented on Figure 1. The groundwater flow direction is





Mr. Jon Clark December 26, 1996 A-8397-06 Page 2

inferred to the northeast and the average hydraulic gradient was 0.04 feet/foot. This is generally the same as in August 1996.

The inferred flow direction is somewhat more easterly and the gradient slightly higher than in observations made previous to August 1996. This is due to a higher relative groundwater elevation measured at MW-3, which was also observed in August 1996. If the groundwater flow direction becomes more easterly, an additional monitoring point may be required between MW-2 and MW-4 so that observations can be made directly down-gradient from the hydrocarbon recovery area. However, at this time, the location of MW-2 appears to be sufficient.

HYDROCARBON THICKNESS AND RECOVERY

The hydrocarbon thickness in MW-1 is presented in Table 1, and a comparison between hydrocarbon thickness and groundwater elevation is presented in Figure 3. Hydrocarbon thickness on November 20, 1996 was 0.32 feet.

Product recovery is summarized in Table 2. Over this period, 6.7 gallons of product were recovered, and a total of 26.7 gallons of fuel has been collected since the inception of hydrocarbon recovery.

PURGE WATER OBSERVATIONS

No odor or sheen was observed in the purge water from MW-2, MW-3, or MW-4.

LABORATORY ANALYSES RESULTS

The results of BTEX laboratory analyses are summarized in Table 3a. No BTEX was detected in any of the monitoring wells sampled. The DRO results (Table 3b) ranged from 0.12 mg/L in MW-2 (ND less than 0.10 in the field duplicate labeled MW-5) to ND in MW-3. All laboratory reports are presented in Appendix B along with a review of data quality.

Data Validation

Laboratory Quality Control Data provided by NCA on groundwater samples collected at AFD-4 indicated that reported results met the data quality objectives outlined in the Hart Crowser Quality Assurance Program Plan; all data are accepted. Any deviations are discussed in Appendix B.



Mr. Jon Clark December 26, 1996 A-8397-06 Page 3

CONCLUSIONS

Hydrocarbon recovery should be continued through the winter because anticipated falling groundwater levels should increase the hydrocarbon thickness in the recovery wells until snowmelt occurs, generally in April. After that time, we recommend that a soil vapor extraction test be conducted to remove the residual hydrocarbons from the subsurface soils.

Since August 1994, data collected from MW-2, MW-3, and MW-4 shows that no dissolved BTEX constituents have reached the down-gradient edge of the site (MW-2) or impacted the area around the former UST excavation. In addition, the DRO concentrations detected in the monitoring wells are low, and no sheen or odor has been observed in the purge water. We recommend that a letter be presented to ADEC requesting that quarterly sampling be reduced to semi-annual events, to occur in January and July of each year, during the duration of this project.

INFORMATION LIMITATIONS

Work for this project was performed, and this letter report prepared, in accordance with generally accepted professional practices for the nature and conditions of the work completed in the same and similar localities at the time the work was performed. It is intended for the exclusive use of MOA. This letter report is not meant to represent a legal opinion, and no other warranty, express or implied, is made.

We trust that this report meets your needs. Any questions regarding the field work and this letter report, the presentation of the information, and the interpretation of the data are welcome and should be referred to Nino Muniz at (907) 276-7475.

Sincerely,

HART CROWSER, INC.

Herminio R. Muniz Sr. Project Hydrogeologist

HRM/mm

Ref:J:\PROJECT\839706\AFD4N96.DOC

Mark G. Madden, P.E.

Senior Associate



Mr. Jon Clark December 26, 1996 A-8397-06 Page 4

Attachments: Table 1
Table 2
Table 3a
Table 3b
Table 3b
Figure 1
Figure 2
Figure 3
Figure 4
Figure 3
Figure 4
Figure 3
Figure 4
Figure 5
Figure 4
Figure 5
Figure 4
Figure 5
Figure 6
Figure 6
Figure 6
Figure 7
Figure 8
Figure 8
Figure 8
Figure 8
Figure 8
Figure 9
Figure 9
Figure 9
Figure 9
Figure 1
Figure 1
Figure 2
Figure 3
Figure 1
Figure 2
Figure 3
Figure 3
Figure 2
Figure 3
Figure 3
Figure 3
Figure 4
Figure 4
Figure 4
Figure 5
Figure 6
Figure 6
Figure 7
Figure 7
Figure 7
Figure 8
F

Appendix A Field Explorations Methods and Analyses

Appendix B Laboratory Reports

A-8397-06

Table 1: Groundwater Elevations and Hydrocarbon Thickness in MW-1 AFD - 4

Anchorage, Alaska

Data	Depth to Hydrocarbon	Depth to Groundwater	Corrected Groundwater Elev.	Hydrocarbon Thickness
Date	(Feet)	(Feet)	(Feet) {1} {2}	(Feet)
8/1/94	Not Observed	10.30	89.07	0.00
8/10/94	9.73	10.58	89.50	0.85
9/8/94	9.99	11.86	89.08	1.87
1/24/95	10.69	13.43	88.24	2.74
1/27/95	10.77	13.33	88.19	2.56
2/3/95	10.99	12.19	88.19	1.20
2/10/95	10.97	12.15	88.21	1.18
2/15/95	10.85	11.97	88.34	1.12
2/24/95	10.88	12.09	88.30	1.21
3/9/95	11.03	12.33	88.13	1.30
3/27/95	11.20	12.56	87.95	1.36
1/21/95	9.34	9.92	89.94	0.58
/22/95	7.86	8.19	91.46	0.33
5/12/95	8.29	8.60	91.03	0.31
7/7/95	8.83	9.19	90.48	0.36
7/17/95	9.02	9.35	90.30	0.33
7/27/95	8.57	8.96	90.74	0.39
8/3/95	8.08	8.44	91.23	0.36
3/29/95	8.60	8.95	90.71	0.35
0/28/95	8.43	8.81	90.88	0.38
0/25/95	8.68	9.05	90.63	0.37
1/21/95	9.11	9.51	90.20	0.40
2/22/95	9.74	10.47	89.51	0.73
/24/96	10.15	10.85	89.11	0.70
1/18/96	9.56	10.35	89.68	0.79
/10/96	8.90	9.27	90.41	0.37
7/3/96	7.92	8.18	91.41	0.26
7/31/96	7.54	7.84	91.78	0.30
8/6/96	7.46	7.75	91.86	0.29
1/20/96	7.50	7.82	91.82	0.32

Notes

prodlvl.xls

^{1} Vertical Survey conducted on 7/2/94; elevation of 100.00 assumed at northeast corner of concrete flagpole footing. MW-1 measuring point elevation =99.37

^{2} Groundwater elevation corrected using measured hydrocarbon specific gravity of 0.84 as determined by laboratory.

Table 2: Hydrocarbon Recovery Record for RW-1 and RW-2 AFD-4

A	Anchorage, Alaska					
ļ	Recovery Well RW-1	Cumulative	Cumulative	Recovery Well RW-2	Cumulative	Cumulative
Dates	(Onuces)	(Onnces)	(Gallons)	(Onuces)	(Onuces)	(Gallons)
1/25/95 - 2/15/95	328	328	2.6	0	0	0
2/16/95 - 3/9/95	55	383	3.0	0	0	0
3/10/95 - 3/24/95	7	390	3.0	0	0	0
3/25/95 - 3/29/95	Frozen	390	3.0	0	0	0
3/30/95 - 4/21/95	0	390	3.0	0	0	0
9/22/95-9/28/95	23	413	3.2	436	436	3.4
9/29/95-10/25/95	4	417	3.3	216	652	5.1
10/25/95-11/21/95	18	435	3.4	388	1040	8.1
11/22/95-12/22/95	72	507	4.0	463	1503	11.7
12/23/95-1/24/96	32	539	4.2	108	1611	12.6
6/28/96-7/31/96	45	584	4.6	360	1971	15.4
8/1/96-11/20/96	151	735	5.7	713	2684	21.0
-						totrecv.xls

Hydrocarbon recovery system was out of service from April 22 through September 15, 1995 NOTE:

due to high water levels.

System was down from February through May 1996 due to pumps being frozen into recovery wells.

Table 3a: Groundwater Laboratory Analysis Results - BTEX Anchorage, Alaska AFD-4

				Benzel	Benzene (mg/L) - EPA 5030/8020)/8020			
Monitoring Well	8/1/94	1/25/95	4/21/95	7/27/95	10/26/95	1/24/96	\$/10/96	96/9/8	11/20/96
MW-1 Field Duplicate	2.3	N/S {2}	S/N	S/N	S/N	S/N	S/N	S/N	S/N
MW-2 Field Duplicate	ND(0.0005) {1}	N/S{3}	ND(0.0005) ND(0.0005)	ND(0.0005) ND(0.0005)	ND(0.0005) ND(0.0005)	ND(0.0005) ND(0.0005)	ND(0.0005) ND(0.0005)	ND(0.0005) ND(0.0005)	ND(0.0005) ND(0.0005)
MW-3 Field Duplicate	ND(0.0005)	ND(0.0005) ND(0.0005)	N/S{4}	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)
MW-4	0.0005	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)
Trip Blank	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)	ND(0.0005)
Monitoring				Total B7	Total BTEX (mg/L) - EPA 5030/8020	30/8020			
Well	8/1/94	1/25/95	4/21/95	7/27/95	10/26/95	1/24/96	5/10/96	96/9/8	11/20/96
MW-1 Field Duplicate	38	S/N	S/N	S/N	S/N	S/N	S/N	S/N	N/S
MW-2 Field Duplicate	0.003	N/S	ND ND	N ON	N ON	0.0006 ND	N ON	ND ON	N ON
MW-3 Field Duplicate	0.006	N ON	S/N	ND	QN	ND	QN	ND	QN
MW-4	0.004	ND	ND	QN	Q	ND QN	N Q	ND	ND
Trip Blank	ND	ND	ND	ND	ND	ND	ND	ND	ND
NOTES: {1} N	NOTES: {1} ND(0.0005) - Not Detected (Detection Limit)	ed (Detection Limit)							H2OBTEX.XLS

N/S - Not sampled due to floating hydrocarbons in well.
 N/S - Not sampled due to large snowpile over well.
 N/S - Not sampled due to ice blockage in well riser.

Table 3b: Groundwater Laboratory Analysis Results - DRO Anchorage, Alaska AFD-4

NOTES:

ND(0.0005) - Not Detected (Detection Limit)


N/S - Not sampled due to floating hydrocarbon in well.
 N/S - Not sampled due to ice blockage in well riser.

Site Plan and Water Table Elevations on November 20, 1996 AFD-4

0

0

Anchorage, Alaska



LEGEND

91.82 0

89 /

0



12/96

A-8397-06 Figure 1

*Corrected for 0.32 feet of free-phase hydrocarbon.

CICR 12/19/96 1=30 8367\ML112096 SCALE IN FEET

09

30

15

Hart Crowser A-8397-06

APPENDIX A FIELD EXPLORATIONS METHODS AND ANALYSES

-00307

APPENDIX A FIELD EXPLORATIONS METHODS AND ANALYSES

This appendix documents the field methods used by Hart Crowser in determining the nature of the conditions underlying the project site addressed by this report. The discussion includes information on the following subjects:

- Water/Floating Hydrocarbon Level Measurements
- Water Quality Sampling
- Petro-trap Operations
- Decontamination of Field Equipment

Water/Floating Hydrocarbon Level Measurements

The water level and floating hydrocarbon in each well was measured from a reference point or "measuring point" marked on the PVC casing. A Flexidip electronic oil/water interface well sounder was used to make the measurements, which were recorded to an accuracy of \pm 0.01 feet.

Water Quality Sampling

Monitoring wells were purged immediately prior to sampling until a minimum of three casing volumes of water were removed. All purge water was containerized. Purging and sampling was performed by lowering a factory decontaminated disposable bailer into the well with single-use polypropylene rope. Samples were collected in 40-ml clear-glass, VOA vials, fitted with TEFLON septa, and 1-Liter brown bottles (when appropriate) provided by the laboratory. A duplicate sample was collected for each well sampling event. Immediately after collection, the samples were labeled and placed in a cooler with "blue-ice" for shipment to NCA laboratory under chain-of-custody procedures.

Petro-trap Operations

Petro-trap hydrocarbon collectors were placed in recovery wells with their screened sections within the floating hydrocarbon zone. Hydrocarbon collection was performed by slowly removing the Petro-trap from the recovery well, and emptying its contents into a graduated container. The Petro-trap was then slowly lowered back into position in the well.

The hydrocarbon quantity was read from the graduated container and recorded on a log sheet. Hydrocarbons were then placed in a 55-gallon drum.

Equipment Decontamination

The Flexi-dip interface probe was cleaned prior to and between sampling attempts using an anionic detergent wash (Alconox) followed by two potable water rinses.

Hart Crowser A-8397-06

APPENDIX B LABORATORY REPORTS

APPENDIX B QUALITY CONTROL NARRATIVE

All field and laboratory quality control criteria regarding the groundwater samples collected and analyzed for this project meet the quality control/quality assurance objectives as stated in Hart Crowser's Standard Quality Assurance Program Plan, dated September 7, 1994, except for the following:

No relative percent difference could be calculated for DRO because the sample MW-2 had a concentration of 0.12 mg/L. The duplicate sample, labeled MW-5, did not have a detectable concentration at a detection limit of 0.10 mg/L. Because the MW-2 concentration was just above the detection limit, we accept the data.

Ref:J:\PROJECT\839706\AFD4APB.DOC





Hart Crowser, Inc. - Alaska 2550 Denali Street, Ste 705 Anchorage, AK 99503 Project: AFD#4
Project Number: A-8397-06

Sampled: 11/20/96 Received: 11/22/96

Project Manager: Nino Muniz

Reported: 12/5/96 15:08

ANALYTICAL REPORT FOR SAMPLES:

Sample Description	Laboratory Sample Number	Sample Matrix	Date Sampled
MW-2	B611410-01	Water	11/20/96
MW-3	B611410-02	Water	11/20/96
MW-4	B611410-03	Water	11/20/96
MW-5	B611410-04	Water	11/20/96
Trip Blank	B611410-05	Water	11/20/96

RECEIV

DEC 1 1 1996

HARI - CKUYVOEK, INC.

North Creek Analytical, Inc.

The results in this report apply to the samples analyzed in accordance with the chain of custody document.

This analytical report must be reproduced in its entirety.





Hart Crowser, Inc. - Alaska 2550 Denali Street, Ste 705 Anchorage, AK 99503 Project: AFD#4
Project Number: A-8397-06
Project Manager: Nino Muniz

Sampled: 11/20/96 Received: 11/22/96

Reported: 12/5/96 15:08

Diesel Hydrocarbons (C10-C28) by EPA Method 8100 (modified) North Creek Analytical - Bothell

	Batch	Date	Date	Surrogate	Reporting			
Analyte	Number	Prepared	Analyzed	Limits	Limit	Result	Units	Notes
MW-2			B6114	10-01			Water	
Diesel Range Hydrocarbons	1160684	11/22/96	11/25/96		0.10	0.12	mg/l	1
Surrogate: 2-FBP	"	"	"	50.0-150		72.5	%	
MW-3			B6114	10-02			Water	
Diesel Range Hydrocarbons	1160684	11/22/96	11/25/96		0.10	ND	mg/l	
Surrogate: 2-FBP	"	"	"	50.0-150		8.01	%	
MW-4			B6114	10-03			Water	
Diesel Range Hydrocarbons	1160684	11/22/96	11/25/96		0.10	0.11	mg/l	1
Surrogate: 2-FBP	"	"	"	50.0-150		66.8	%	
<u>MW-5</u>			B6114	10-04			Water	
Diesel Range Hydrocarbons	1160684	11/22/96	11/25/96		0.10	ND	mg/l	
Surrogate: 2-FBP	"	"	"	50.0-150		61.6	%	

North Creek Analytical, Inc.

*Refer to end of report for text of notes and definitions.





Hart Crowser, Inc. - Alaska 2550 Denali Street, Ste 705 Anchorage, AK 99503 Project: AFD#4
Project Number: A-8397-06
Project Manager: Nino Muniz

Sampled: 11/20/96 Received: 11/22/96

er: Nino Muniz Reported: 12/5/96 15:08

BTEX by EPA Method 8020A North Creek Analytical - Bothell

	Batch	Date	Date	Surrogate	Reporting			
Analyte	Number	Prepared	Analyzed	Limits	Limit	Result	Units	Notes'
MW-2			B6114	10-01			Water	
Benzene	1160799	11/27/96	11/27/96		0.500	ND	ug/l	
Toluene		11	"		0.500	ND	"8"-	
Ethylbenzene	ii a	11	"		0.500	ND	n	
Xylenes (total)	n =	11	"		1.00	ND		
Surrogate: 4-BFB (PID)	"	"	"	53.0-136		88.1	% -	
<u>MW-3</u>			B61141	10-02			Water	
Benzene	1160799	11/27/96	11/27/96		0.500	ND	ug/l	
Toluene	n	"	n		0.500	ND	"	
Ethylbenzene	"	"	п		0.500	ND	"	
Xylenes (total)	"	"	"		1.00	ND	n —	
Surrogate: 4-BFB (PID)	"	"	"	53.0-136		90.0	%	
MW-4			B61141	10-03			Water	
Benzene	1160799	11/27/96	11/27/96		0.500	ND	ug/l	
Toluene	"	11	"		0.500	ND	,, _	
Ethylbenzene	"	"	"		0.500	ND	ü	
Xylenes (total)	11	"	11		1.00	ND	•	
Surrogate: 4-BFB (PID)	"	"	"	53.0-136		83.7	%	
<u>MW-5</u>			B61141	0-04			Water	
Benzene	1160799	11/27/96	11/27/96		0.500	ND	ug/l	
Toluene	"	"			0.500	ND	, ~	
Ethylbenzene	11	11	н		0.500	ND	"	
Xylenes (total)	***	"	п		1.00	ND	n	
Surrogate: 4-BFB (PID)	"	"	"	53.0-136		85.0	%	
Trip Blank			B61141	0-05			Water	
Benzene	1160799	11/27/96	11/27/96		0.500	ND	ug/l	
Toluene	"	"	"		0.500	ND	"	
Ethylbenzene	"	"	"		0.500	ND	n	
Xylenes (total)	HII	"	n		1.00	ND	и	
Surrogate: 4-BFB (PID)	"	"	"	53.0-136		86.3	%	

North Creek Analytical, Inc.

*Refer to end of report for text of notes and definitions.



BOTHELL = (206) 481-9200 = FAX 485-2992 SPOKANE = (509) 924-9200 = FAX 924-9290

PORTLAND **(503)** 643-9200 **FAX** 644-2202

Hart Crowser, Inc. - Alaska 2550 Denali Street, Ste 705 Anchorage, AK 99503 Project: AFD#4
Project Number: A-8397-06

Sampled: 11/20/96 Received: 11/22/96

Project Manager: Nino Muniz

Reported: 12/5/96 15:08

Diesel Hydrocarbons (C10-C28) by EPA Method 8100 (modified)/Quality Control North Creek Analytical - Bothell

	Date	Spike	Sample	QC		Reporting Limit	Recov.	RPD	RPD	
Analyte	Analyzed	Level	Result	Result	Units	Recov. Limits	%	Limit	%	Notes*
Batch: 1160684	Date Prepa	red: 11/22	/96		Extract	tion Method: EP.	A 3520/6	00 Series		
Blank	1160684-BI	LK1	= =							
Diesel Range Hydrocarbons	11/25/96			ND	mg/l	0.10				
Surrogate: 2-FBP	"	0.344		0.271	"	50.0-150	78.8	·		
LCS	1160684-BS	<u>51</u>								
Diesel Range Hydrocarbons	11/25/96	2.04		1.64	mg/l	54.0-121	80.4			
Surrogate: 2-FBP	"	0.344		0.236	"	50.0-150	68.6			
LCS Dup	1160684-BS	SD1								
Diesel Range Hydrocarbons	11/25/96	2.04		1.50	mg/l	54.0-121	73.5	20.0	8.97	
Surrogate: 2-FBP	"	0.344		0.212	"	50.0-150	61.6			

North Creek Analytical, Inc.

*Refer to end of report for text of notes and definitions.



Hart Crowser, Inc. - Alaska 2550 Denali Street, Ste 705 Anchorage, AK 99503 Project: AFD#4
Project Number: A-8397-06
Project Manager: Nino Muniz

Sampled: 11/20/96 Received: 11/22/96

Reported: 12/5/96 15:08

BTEX by EPA Method 8020A/Quality Control North Creek Analytical - Bothell

	Date	Spike	Sample	QC		Reporting Limit	Recov.	RPD	RPD
Analyte	Analyzed	Level	Result	Result	Units	Recov. Limits	%	Limit	% Notes
Batch: 1160799	Date Prepa	red: 11/27	/96		Extrac	tion Method: EPA	A 5030		
Blank	1160799-BI	LK1							
Benzene	11/27/96			ND	ug/l	0.500			
Toluene	n			ND	"	0.500			
Ethylbenzene	n			ND	**	0.500			
Xylenes (total)	"			ND	"	1.00			
Surrogate: 4-BFB (PID)	"	16.0		13.6	"	53.0-136	85.0		
Matrix Spike	1160799-M	S1 Be	511410-01						
Benzene	11/27/96	10.0	ND	8.91	ug/l	62.0-126	89.1		
Toluene	"	10.0	ND	8.74	**	72.0-120	87.4		
Ethylbenzene		10.0	ND	8.95	**	69.0-129	89.5		
Xylenes (total)	"	30.0	ND	26.8	"	73.0-126	89.3		
Surrogate: 4-BFB (PID)	"	16.0		15.2	"	53.0-136	95.0		
Matrix Spike Dup	1160799-M	SD1 Be	611410-01						
Benzene	11/27/96	10.0	ND	8.91	ug/l	62.0-126	89.1	13.5	0
Toluene		10.0	ND	8.74	"	72.0-120	87.4	8.70	0
Ethylbenzene	"	10.0	ND	8.73	11	69.0-129	87.3	13.6	2.49
Xylenes (total)	"	30.0	ND	26.2	"	73.0-126	87.3	16.3	2.27
Surrogate: 4-BFB (PID)	"	16.0		14.2	"	53.0-136	88.7		252-25-25-25

North Creek Analytical, Inc.

*Refer to end of report for text of notes and definitions.





Hart Crowser, Inc. - Alaska 2550 Denali Street, Ste 705 Anchorage, AK 99503

Project: AFD#4 Project Number: A-8397-06 Nino Muniz

Sampled: 11/20/96 Received: 11/22/96

Project Manager:

Reported: 12/5/96 15:08

Notes and Definitions

Note The sample chromatographic pattern does not resemble the fuel standard used for quantitation. A fuel fingerprint is advised. DET Analyte DETECTED ND Analyte NOT DETECTED at or above the reporting limit Not Reported NR Sample results reported on a dry weight basis Recov. Recovery RPD Relative Percent Difference

North Creek Analytical, Inc.

B611410

Sample Custody Record

2550 Denali Street, Suite 705 Anchorage, AK 99503-2737 Phone: 907-276-7475 FAX: 907-276-2104 Hart Crowser, Inc.

HARTCROWSER

0317 cotel/lorms/custody COMPOSITING INSTRUCTIONS OBSERVATIONS/COMMENTS/ TOTAL NUMBER OF CONTAINERS N/A SAMPLE RECEIPT INFORMATION CUSTODY SEALS: STANDARD OVERNIGHT 1 WEEK SHIPMENT METHOD: HAND OTHER 2 TURNAROUND TIME: GOOD CONDITION

YES TEMPERATURE: 24 HOURS 48 HOURS 72 HOURS COURIER NO. OF CONTAINERS 3 3 5 STORAGE LOCATION: REQUESTED ANALYSES Results to Nino Mon. 2 SPECIAL SHIPMENT/HANDILING OR for Other Contract Requirements STORAGE REQUIREMENTS: See Lab Work Order No. COOLER NO.: 230 2318 X X X318 555 × × × Lab to Return White Copy to Hart Crowser TIME | MATRIX 11 20 % 2:00 W. S. 1/22/96 0900 DATE TIME DATE TIME 33 3 2:3tp DATE RECEIVED BY MUNIT RECEIVED BY LAB NUMBER PRINT NAME SIGNATURE DESCRIPTION COMPANY Pink to Project Manager 2,20 11/21/18 May Plyn T # OJY TIME DATE 9:04 TIME JOB NUMBER A-5337 OC ALCIO GUIGA HART CROWSER CONTACT SAMPLE ID -03 mm-4 -Offmo S 811410-01/MJ-2 -02/mc 3 White and Yellow Copies to Lab RELINQUISHED BY SIGNATURE (CULLA RELINQUISHED BY PRINT, NAME / THE COMPANY PROJECT NAME SAMPLED BY: LAB NO. PRINT NAME SIGNATURE COMPANY