

March 1,2015

DRAFT This tactic map is a working draft being used to develop a Geographic Response Strategy at this location. The tactics represented here have not been approved by the Subarea Committee and should not be considered final. If you have questions or comments please contact us by email at contact@nukaresearch.com.

NUKA Research & Planning Group, LLC.

## Aleutian Subarea Geographic Response Strategies

| ID        | Location and Description  | <b>Response Strategy</b>  | Implementation   | Response Resources   | Staging Area       | Site Access                         | Resources Protected<br>(months)  | Special<br>Considerations  |
|-----------|---|---|--|--|--------------------|-------------------------------------|--|--|
| AWB-01-01 | Kiska Harbor           Trout Lagoon           a.         Lat. 51° 58.447'N           Lon. 177° 32.106'E           b.         Lat. 51° 57.858'N           Lon. 177° 32.067'E           c.         Lat. 51° 58.986'N           Lon. 177° 32.860'E | <b>Passive Recovery</b><br>Use passive recovery for rapid<br>deployment prior to oil impacts<br>and the arrival of hard boom.<br>Place passive recovery boom<br>across the entrance to the salmon<br>streams in Kiska Harbor. Move<br>the boom to maximize the<br>protection of the salmon streams. | If oil impacts are expected prior to the deployment of other<br>tactics, place and anchor snare line or sorbent boom across<br>the identified creek mouths. Passive recovery boom may<br>be deployed behind the fast-water boom.<br>Move to arrays further back into the streams if the sea<br>state precludes deployment.<br>Replace as necessary to maximize the recovery.<br><u>Boom Lengths:</u><br>a. 450 ft.<br>b. 100 ft.<br>c. 100 ft. | Deployment<br>Equipment<br>650 ft. snare line or sorbent boom<br>3 ea. small anchor systems<br>12 ea. anchor stakes<br>Vessels/Personnel/Shift<br>Same as AWB-01-02<br>Tending<br>Vessels/Personnel/Shift<br>Same as AWB-01-02   | Vessel<br>Platform | Via marine<br>waters<br>Chart 16442 | Same as AWB-01-02  | Vessel master should<br>have local<br>knowledge.<br>Title 16 permitting<br>required from ADFG.<br>Title 41 permitting<br>required from ADNR  |
| AWB-01-02 | Kiska Harbor- Trout<br>Lagoon<br>Lat. 51° 58.447'N<br>Lon. 177° 32.106'E  | <b>Diversion / Recovery</b><br>Divert oil entering Trout Lagoon<br>to beach for recovery.   | Use class 6 vessels to place 450 ft. of fast-water boom<br>with shore seal on the collection end across the entrance of<br>Trout Lagoon for shoreside recovery. Place boom in front<br>of the pre<br>Set up collection unit and tend throughout the tide.  | DeploymentEquipment450 ft. fast-water/harbor boom3 ea. small anchor systems8 ea. anchor stakes1 ea. shoreside collection unitVessels1 ea. class 32 ea. class 6Personnel/Shift7 ea. vessel crew2 ea. response techsTendingVessels1 ea. class 31 ea. class 4Personnel/Shift4 ea. vessel crew4 ea. vessel crew5 vessels1 ea. class 51 ea. class 6Personnel/Shift4 ea. vessel crew | Vessel<br>Platform | Via marine<br>waters<br>Chart 16442 | Marine mammals: sea<br>otter, seal<br>Fish: pink salmon,<br>dolly varden<br>Birds: waterfowl<br>concentrations, seabird<br>nesting<br>Habitat: exposed<br>rocky shore, marsh | Vessel master should<br>have local<br>knowledge.<br>Site Survey- Not<br>surveyed<br>Tested- Not yet<br>Fast-water boom is<br>specified for<br>logistical<br>considerations<br>(weight and<br>portability) for this<br>remote deployment. |
| AWB-01-03 | Kiska Harbor<br>a. Lat. 51° 57.858'N<br>Lon. 177° 32.067'E<br>b. Lat. 51° 58.986'N<br>Lon. 177° 32.860'E  | <b>Exclusion</b><br>Exclude oil from impacting the<br>salmon streams in Kiska Harbor.   | <ul> <li>Deploy anchors and boom with skiffs (class 6).</li> <li>Exclude the entrance to the streams with fast-water boom.</li> <li>Place the boom in a chevron pattern extending into the ocean. If the sea state precludes this is strategy, deploy further back in the stream.</li> <li>Tend throughout the tide.</li> <li><u>Boom Lengths:</u></li> <li>d. 100 ft.</li> <li>e. 100 ft.</li> </ul>  | Deployment<br>Equipment<br>200 ft. fast-water boom<br>2 ea. small anchor systems<br>8 ea. anchor stakes<br>Vessels/Personnel/Shift<br>Same as AWB-02-02<br>Tending<br>Vessels/Personnel/Shift<br>Same as AWB-02-02   | Vessel<br>Platform | Via marine<br>waters<br>Chart 16442 | Same as AWB-01-02  | Vessel master<br>121should have local<br>knowledge.<br>Site Survey- Not<br>surveyed<br>Tested- Not yet   |
| AWA-01-04 | Kiska Harbor<br>Nearshore waters in the<br>general area of:<br>Lat. 51° 58.001'N<br>Lon. 177° 34.246'E  | <b>Free-oil Recovery</b><br>Maximize free-oil recovery in the<br>offshore & nearshore<br>environment of Kiska Harbor<br>depending on spill location and<br>trajectory.  | Deploy free-oil recovery strike teams upwind and up<br>current of Kiska Harbor.<br>Use aerial surveillance to locate incoming slicks.  | Deploy multiple free-oil recovery<br>strike teams as required to<br>maximize interception of oil<br>before it impacts sensitive areas.   | Adak- 220 nm       | Via marine<br>waters<br>Chart 16442 | Same as AWB-01-02  | Vessel master should<br>have local<br>knowledge.   |

AWB-01