

# Department of Environmental Conservation

**DIVISION OF WATER** 

Wastewater Discharge Authorization Program

555 Cordova Street Anchorage, Alaska 99501-2617 Main: 907.269.6285 Fax: 907.334.2415

www.dec.alaska.gov/water/wwdp

April 18, 2022

Konstantin Konstantinov Holland America Group 601 W 5<sup>th</sup> Ave, #501 Anchorage, AK 99501

Re: Authorization to Discharge 2013DB0004-0006: Crown Princess

#### Dear Mr. Konstantinov:

The Alaska Department of Environmental Conservation (DEC) has completed its review and acknowledges that you have submitted a complete Notice of Intent (NOI) form for the 2013DB0004 Large Commercial Passenger Vessel Wastewater Discharge General Permit (Permit).

The Crown Princess is hereby authorized to discharge treated wastewater into Alaska marine waters and is issued wastewater discharge authorization number <u>2013DB0004-0006</u>. Discharge from this vessel is authorized in accordance with the terms and conditions of the general permit and any vessel-specific conditions included in this document.

An electronic copy of the Permit and this authorization is available at the Department website <a href="http://dec.alaska.gov/water/cruise-ships/cruise-general-permit/">http://dec.alaska.gov/water/cruise-ships/cruise-general-permit/</a>.

### The following are vessel specific conditions that apply to this authorization:

- 1) Treated wastewater discharge is authorized when the vessel is operating at speeds of 6 knots or greater.
  - a. Mixing Zone: Mixing zone size for the permittee is authorized for discharges at speeds of 6 knots or greater and is limited to 63 meters in length, 5 meters in width, and a depth from the water surface to the depth the discharge port is below the water surface plus one meter. The shape of the mixing zone is an elongated rectangle that extends from the discharge port towards the stern of the ship. See Permit Section 5.2.3.
  - b. Effluent Limits and sampling requirements are identified in Tables 3 and 5 of the Permit
- 2) Treated wastewater discharge is authorized when the vessel is operating at speeds of less than 6 knots.
  - a. Mixing Zone: Mixing zone size for permittees authorized for discharges at speeds under 6 knots, excepted as specified in Section 5.2.5, is limited to a radius of 83 meters and a depth from the water surface to the depth the discharge port is below the water surface plus one meter. The mixing zone will extend away from the hull of the vessel in a semicircle centered on the discharge port. See Permit Section 5.2.4.
  - b. In-port discharge is only authorized from a single port that is located on the outboard side of the vessel from the dock.
  - c. Effluent Limits and sampling requirements are identified in Tables 4 and 6 of the Permit.
  - d. Receiving Water Monitoring is required twice per year in accordance with Permit Section 6.9.3.
- 3) Discharge from multiple ports simultaneously is prohibited.

2022DB0004-0006 4/18/2022

The permittee is reminded of the following permit requirements, and is responsible for all submissions and activities in the Permit even if they are not summarized below:

- All Commercial Passenger Vessels must register annually see Permit Part <u>2.1.3</u>. <a href="http://dec.alaska.gov/water/cruise-ships/cruise-registration/">http://dec.alaska.gov/water/cruise-ships/cruise-registration/</a>.
- As per Permit Part <u>4.2.3</u>, the permittee shall notify the Department, in writing, of wastewater treatment system modifications that change information provided to the Department in the approved NOI form at least 48 hours prior to the discharge of any treated wastewater into marine waters of the state. The NOI Application form can be accessed at the Departments website <a href="http://dec.alaska.gov/water/cruise-ships/cruise-general-permit/">http://dec.alaska.gov/water/cruise-ships/cruise-general-permit/</a>.
- Quality Assurance Project Plan (QAPP) see Permit Part 6.1: The owner/operator of a vessel that
  intends to discharge wastewater into Alaskan waters must submit a wastewater sampling QAPP to
  ADEC for approval.
- Vessels Specific Sampling Plan (VSSP) see Permit Part <u>6.2</u>: All vessels are required to have an approved Vessel Specific Sampling Plan (VSSP) 21 days before sampling.
- Sampling requirements for discharges underway at speeds greater than 6 knots and associated effluent limits can be found in Tables 2, 3 and 5 of the permit.
- Sampling requirements for discharges at speeds less than 6 knots and associated effluent limits are located in Tables 4 and 6 of the permit.
- Discharge Monitoring Reports (DMRs): see Permit Part 7.2: DMRs are required for each calendar month that the vessel operated in the marine waters of the state and must be submitted within the first 21 days of the following calendar month.
- Submit all CPVEC registration correspondence, support documents, and reports to: <u>DEC.WQ.Cruise@alaska.gov</u> or mail to: ADEC-CPVEC, ATTN: Cruise Ship Program P.O. Box 111800 Juneau, AK 99811-1800.
- A copy of the General Permit 2013DB0004 and this authorization letter must be kept onboard the vessel. This letter does not relieve the permittee from other local, state, or federal government permitting requirements.

Please reference your permit authorization number 2013DB0004-0006 and vessel name in all future correspondence. If you have any questions regarding the above, please contact Sam Kito at 907-269-7542, or via email at <a href="mailto:Sam.Kito@alaska.gov">Sam.Kito@alaska.gov</a>.

Sincerely,

James Rypkema

Program Manager, Cruise Ship Permitting

Enclosure: NOI

cc: DEC.WQ.Cruise@alaska.gov



# NOTICE OF INTENT FORM

Notice of Intent to be covered under the Wastewater General Perr Commercial Passenger Vessels Operating in Alaska (See Sections 2	•	
Submission of this document constitutes a request that certain discharges into marine waters of the state resulting from the operation of the large commercial passenger vessels identified herein be authorized under General Permit 2013-DB0004.		
Vessel Owner Information		
Who is the main point of contact for the vessel? (e.g. owner, operator	tor, or Alaska Agent):	
Vessel Owner's Business Name: Princess Cruise Line, Ltd.		
Mailing Address: 24305 Town Center Drive Santa Clarita, CA 91355	Phone: 661 753 2724	
Representative: Konstantin Konstantinov	Email: kkonstantinov@hagroup.com	
Vessel Owner's or Operator's Alaska Agent Information		
Company Name: Holland America Group		
Mailing Address: 601 W 5 <sup>th</sup> Avenue #501, Anchorage, AK 99501	Phone: 907-264-2128	
Representative: Ralph Samuels	Email: rsamuels@hollandamericagroup.com	
Vessel Operator's Business Name if Different From the Owner's Bu	siness Name	
Vessel Operator's Business Name: Same as "Owner"		
Mailing Address:	Phone:	
Representative:	Email:	

Vessel Information (Y/N)			
Are you seeking authorization to discharge with a mixing zone?			Υ
Are you seeking authorization to discharge while moving at 6 knots or greater?			Υ
Are you seeking authorization to dis	charge v	while moving at under 6 knots?	Υ
Are you seeking authorization to dis-	charge v	while in Skagway at Broadway or Ore Docks?	N
If the permittee is seeking authorize	ation wh	nich includes a mixing zone, attach (may be en	nailed
		s the length of the vessel and the locations of	
wastewater effluent penetration po	oints (po	rts) on the hull.	
Vessel Name:		Crown Princess	
Vessel IMO Number:		9293399	
Vessel Gross Tonnage:		113561	
Port of Registry:		Hamilton, Bermuda	
Maximum Passenger Capacity per Voyage:		3599	
Maximum Crew Capacity per Voyage:		1201	
Vessel Draft <sup>1</sup> :		8.6 meters	
Vessel Length in Meters at Waterline <sup>2</sup> :		288.7	
Vessel Tracking			
Method of submitting hourly vessel	tracking	information while in Alaskan waters (Marine E	xchange
of Alaska AIS or other Department a	pproved	method):	
Name, physical address, and	Marine Exchange of Alaska		
mailing addresses of the service:	1050 Harbor Way		
	Juneau, AK 99801		
Contact's name, email address,	Marine Exchange of Alaska		
and phone number:	907-463-2607		
	INFO@MXAK.ORG		

<sup>&</sup>lt;sup>1</sup> Vessel draft under a) loaded condition for Alaska operations (bunkers / waste water storage etc.) and b) under light ship conditions for Alaska operations (bunkers empty / no waste water storage etc.)

<sup>&</sup>lt;sup>2</sup> Length of Waterline (LWL) under normal load in standard Alaska conditions.

Discharge Port Characteristics				
Note: If there is more th	Note: If there is more than one discharge port attach a sheet with the characteristics below for			
each AWTS Port. If more	each AWTS Port. If more than one discharge pump attach sheet with capacity for each.			
Discharge Port	Discharge Port	Leasting (Challes of (Dat))		
Name <sup>3</sup> :	D	Location (Starboard/Port):	Port	
Discharge Port	100 mm	Discharge Port Centerline	6 10 motors	
Internal Diameter:	100 mm	Vertical Distance from Keel:	6.10 meters	
Discharge Port		Discharge Port Centerline		
Distance from Bow at	250 motors	Vertical Distance from	2.50 meters	
Waterline (normal	250 meters Vertical Distance from 2.50 meters Waterline (normal load) <sup>4</sup> :		2.50 meters	
load):		waterline (normal load) .		
Discharge Port shape	Round	Discharge Port Pump Capacity	40 m3/h x 2 pumps	
(round, oval, square):	Kounu	(m³/hr) for each Pump <sup>5</sup> :		
Discharge Port		Discharge Port Horizontal Angle		
Vertical Angle Relative	68 Deg	Relative to Centerline <sup>7</sup> :	88 Deg	
to Waterline <sup>6</sup> :		Relative to Centerline .		

Wastewater Discharge Information				
Estimates of the average and maximum volume of the wastewater to be discharged per 24 hour period (in cubic meters), and the beginning and ending dates between which discharges may occur the first year of the permit;	Average:	740 m3		
	Maximum:	825 m3		
	Startup Date:	05/01/2022		
	Ending date:	09/21/2022		

<sup>&</sup>lt;sup>3</sup> Name or identification as used in VSSP and Waste Water Discharge Logbook.

<sup>&</sup>lt;sup>4</sup> Vertical distance from the vertical centerline of the discharge port relative to the standard (loaded) conditions waterline.

<sup>&</sup>lt;sup>5</sup> Treated wastewater discharge pump for the named discharge port. For vessels with variable speed / capacity pumps identify the effective discharge capacities. For vessels with more than one pump simultaneously operated identify the total effective pump capacities.

<sup>&</sup>lt;sup>6</sup> Parallel with the Vertical Longitudinal Center Plane orientation of the hull orientation angle defined as the angle in degrees between the horizontally perpendicular projected line originating from the vertical longitudinal center plane of the hull self to the center of the discharge port, and the projected perpendicular line originating from the port center self (face) vertically directed to the center plane of the hull (Y-Y axis).

<sup>&</sup>lt;sup>7</sup> Parallel with the Vertical Longitudinal Center Plane orientation of the hull orientation angle defined as the angle in degrees between the horizontally perpendicular projected line originating from the vertical longitudinal center plane of the hull self to the center of the discharge port, and the projected perpendicular line originating from the port center self (face) horizontally directed to the vertical center plane of the hull (X-X axis).

The type, number, and combined maximum design capacity in cubic meters per 24 hour period of all advanced wastewater treatment systems (AWTS) onboard;	Type (s) (including manufacturer, model name, model number, and year built):	Hamworthy Membrane Bioreactor
	Number of AWTS:	3
	Combined design capacity:	975 m3
Type(s) of sewage treatment and system capacity in cubic meters per 24 hour period;	Type (s) (including manufacturer, model name, model number, and year built):	
	Hamworthy Membrane Biore	eactor
	Combined design capacity: 9	75 m3
Type(s) of graywater treatment and system capacity in cubic meters per 24 hour period;	Type (s) (including manufacturer, model name, model number, and year built):	
	Hamworthy Membrane Biore	eactor
	Combined design capacity: 9	75 m3
Average volume of sewage generation per day in cubic meters;	160 m3	
Maximum volume of sewage generation per day in cubic meters;	160 m3	
Average graywater generation per day in cubic meters for the following	Accommodations: 675 m3	
sources;	Galley: 230 m3	
	Laundry: 220 m3	
	Other (list types and volume	s):
Maximum graywater generation per day in cubic meters for the following	Accommodations: 675m3	
sources;	Galley: 230 m3	
	Laundry: 220 m3	
	Other (list types and volume	s):

The method of handling and disposal of sludge and biosolids produced from the treatment of sewage and graywater.

The desludging of MBR systems will take place > 12 NM outside of Alaska permit waters.

## **Signature and Certification for NOI**

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I have no personal knowledge that the information submitted is other than true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fines and imprisonment for knowing violations.

Signature of Responsible Co	rporate Officer	Printed Name
Konstantin	Digitally signed by Konstantin Konstantinov DN: cn=Konstantin Konstantinov, o=Holland America Group, ou=Deputy Director,	Konstantin Konstantinov
Konstantinov	Environmental Operations and Policy,  mail=kkonstantinov@hagroup.com, c=US  Date: 2022.03.02 08:59:52 -08'00'	
Title/Company		Date
Deputy Director, Environmental Operations and Policy, Holland America Group		3/2/2022

### **Submit this Notice of Intent to:**

Commercial Passenger Vessel Environmental Compliance Program
Division of Water
Alaska Dept. of Environmental Conservation
410 Willoughby Avenue, Suite 303
PO Box 111800
Juneau, AK 99811-1800