

Hydrocarbon Fuel Gas [insert into Title-V Permits]

Calculate SO₂ concentration using the equations below:

$$A = [H_2S_{concentration}] \div 1,000,000 = \underline{\hspace{2cm}} \text{ ppmv} \div 1,000,000 = \underline{\hspace{2cm}}$$

$$B = 6.64 \times A = 6.64 \times \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$C = [\text{vol}\% \text{inertgas}_{\text{fuel}}] \div 100\% = \underline{\hspace{2cm}} \% \div 100\% = \underline{\hspace{2cm}}$$

$$D = [\text{vol}\% \text{HC}_{\text{fuel}}] \div 100\% = \underline{\hspace{2cm}} \% \div 100\% = \underline{\hspace{2cm}}$$

$$E = [\text{wt}\% \text{C}_{\text{HC}}] \div 100\% = \underline{\hspace{2cm}} \% \div 100\% = \underline{\hspace{2cm}}$$

$$F = 0.396 \times E = 0.396 \times \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$G = [\text{wt}\% \text{H}_{\text{HC}}] \div 100\% = \underline{\hspace{2cm}} \% \div 100\% = \underline{\hspace{2cm}}$$

$$H = 0.933 \times G = 0.933 \times \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$I = F + H = \underline{\hspace{2cm}} + \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$J = D \times I \times [MW_{\text{HC}}] = \underline{\hspace{2cm}} \times \underline{\hspace{2cm}} \times \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$K = B + C + J = \underline{\hspace{2cm}} + \underline{\hspace{2cm}} + \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$L = 21\% - [\text{vol}\% \text{dryO}_{2,\text{exhaust}}] = 21\% - \underline{\hspace{2cm}} \% = \underline{\hspace{2cm}} \%$$

$$M = [\text{vol}\% \text{dryO}_{2,\text{exhaust}}] \div L = \underline{\hspace{2cm}} \% \div \underline{\hspace{2cm}} \% = \underline{\hspace{2cm}}$$

$$N = 1 + M = 1 + \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$O = K \times N = \underline{\hspace{2cm}} \times \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

$$\text{SO}_2 \text{ concentration} = [H_2S_{concentration}] \div O = \underline{\hspace{2cm}} \text{ ppmv} \div \underline{\hspace{2cm}} = \underline{\hspace{2cm}} \text{ ppmv}$$

List of Abbreviations Used in this Permit [insert into Section 1 of Title-V Permits]

H₂S concentration is the volumetric H₂S concentration of a fuel gas on a dry or wet basis, 10⁶ X gmole-H₂S/gmole-fuel (i.e. ppmv)

MW_{HC} is the molecular weight of the hydrocarbon portion of the fuel gas, g-HC/gmole-HC

SO₂ concentration is the volumetric SO₂ concentration of the exhaust gas on a dry basis, 10⁶ X gmole-SO₂/gmole-air_{exhaust,dry} (i.e. ppmv)

vol%_{dry}O_{2,exhaust} is the volume percent O₂ of the exhaust gas on a dry basis, 100% X gmole-O₂/gmole-dryexhaust

vol%_{HC}fuel is the volume percent hydrocarbons of a fuel gas, 100% X gmole-HC/gmole-fuel

vol%_{H₂O}fuel is the volume percent water vapor of a fuel gas (equals zero if on a dry basis), 100% X gmole-H₂O/gmole-fuel

vol%_{inertgas}fuel is the volume percent inert gas (e.g. N₂ and CO₂) of a fuel gas, excluding water vapor, 100% X gmole-inertgas/gmole-fuel

wt%_CHC is the weight-percent carbon of the hydrocarbon portion of a fuel gas, 100% X g-C/g-HC

wt%_HHC is the weight-percent hydrogen of the hydrocarbon portion of a fuel gas, 100% X g-H/g-HC

For example, a fuel gas on a dry basis is 50-ppm H₂S, 2% CO₂, 3% N₂, and 95% CH₄ (i.e. methane) with $\text{vol}\%_{\text{dry}}\text{O}_{2,\text{exhaust}} = 15\%$. The inputs are:

H₂S concentration = 50 ppm; **MW_{HC}** = 16; **vol%inertgas_{fuel}** = 2 + 3 = 5%;
vol%HC_{fuel} = 95%; **wt%C_{HC}** = 75%; and **wt%H_{HC}** = 25%. (Note that $\text{vol}\%\text{H}_2\text{S}_{\text{fuel}} = 50 / 10,000 = 0.005\%$, that **vol%H₂O_{fuel}** = 0%.) **SO₂concentration** = 1.8 ppmv.

Note that the sum of the following four terms must total 100%: 1)

H₂S concentration converted to a percent by dividing by 10,000 (i.e. $\text{vol}\%\text{H}_2\text{S}_{\text{fuel}}$); 2) **vol%inertgas_{fuel}**; 3) **vol%HC_{fuel}**; and 4) **vol%H₂O_{fuel}**. Note that the sum of **wt%C_{HC}** and **wt%H_{HC}** must total 100%.

ATTACHMENT 1 [insert into Title-V Statements of Bases]

Computational Basis is 1 *gmole* hydrocarbon fuel gas

NOMENCLATURE (in alphabetical order):

- C_{fuel} = number of gram-moles of the carbon part of a fuel gas, *gmole-C*
 $H_{2,\text{fuel}}$ = number of gram-moles of the "equivalent H_2 " part of a fuel gas, *gmole- H_2*
 H_2S_{concent} = volumetric H_2S concentration of a fuel gas on a dry or wet basis, *ration* $10^6 \times gmole-H_2S/gmole-fuel$ (i.e. *ppmv*)
 $mol-CO_2$ = amount of CO_2 in the exhaust gas, *gmole- CO_2*
 $mol-H_2O$ = amount of H_2O in the exhaust gas supplied by the free hydrogen in the fuel gas, excluding water vapor from the fuel gas and excluding water vapor from the ambient air, *gmole- H_2O*
 $mol-O_2$ = amount of O_2 in the exhaust gas, *gmole- O_2*
 $mol-N_2$ = amount of N_2 in the exhaust gas, excluding N_2 from the fuel gas, *gmole- N_2*
 $mol-SO_2$ = amount of SO_2 in the exhaust gas, *gmole- SO_2*
 MW_{HC} = molecular weight of the hydrocarbon part of a fuel gas, *g-HC/gmole-HC*
 $N_{2,c}$ = ambient N_2 accompanying $O_{2,c}$ for combustion, *gmole- N_2*
 N_{2,H_2} = ambient N_2 accompanying O_{2,H_2} for combustion, *gmole- N_2*
 $N_{2,s}$ = ambient N_2 accompanying $O_{2,s}$ for combustion, *gmole- N_2*
 $O_{2,c}$ = ambient O_2 used to combust the carbon part of a fuel gas, *gmole- O_2*
 O_{2,H_2} = ambient O_2 used to combust the H_2 part of a fuel gas, *gmole- O_2*
 $O_{2,s}$ = ambient O_2 used to combust the sulfur part of a fuel gas, *gmole- O_2*
 $part-H_2S$ = fraction of hydrogen-sulfide of a fuel gas, *gmole- $H_2S/gmole-fuel$*
 $part-HC$ = fraction hydrocarbon of a fuel gas, *gmole-HC/gmole-fuel*
 $part-inertgas$ = fraction inert gas (e.g. N_2 and CO_2) of a fuel gas, *gmole-inertgas/gmole-fuel*
 S_{fuel} = number of gram-moles of the sulfur part of a fuel gas, *gmole-S*
 $SO_{2,\text{concent}}$ = volumetric SO_2 concentration of the exhaust gas on a dry basis, *ration* $10^6 \times gmole-SO_2/gmole-dryexhaust$ (i.e. *ppmv*)
 $total-N_2$ = amount of ambient N_2 accompanying $total-O_2$ for combustion, *gmole- N_2*
 $total-O_2$ = total amount of ambient O_2 for combustion plus the excess O_2 , *gmole- O_2*
 $vol\%_{\text{dry}}O_{2,\text{exhaust}}$ = volume percent O_2 of the exhaust gas on a dry basis, $100\% \times gmole-O_2/gmole-dryexhaust$
 $vol\%H_2O_{\text{fuel}}$ = volume percent water vapor of a fuel gas (equals zero if on a dry basis), $100\% \times gmole-H_2O/gmole-fuel$

- vol%HC_{fuel}** = volume percent hydrocarbons of a fuel gas, $100\% \times \text{gmole-HC/gmole-fuel}$
- vol%inertga_{fuel}** = volume percent inert gas (e.g. N₂ and CO₂) of a fuel gas, $100\% \times \text{gmole-inertgas/gmole-fuel}$ excluding water vapor, $100\% \times \text{gmole-inertgas/gmole-fuel}$
- wt%C_{HC}** = dry weight-percent carbon of the hydrocarbon part of a fuel gas (not weight percent carbon of the total fuel gas), $100\% \times \text{g-C/g-HC}$
- wt%H_{HC}** = dry weight-percent hydrogen of hydrocarbon part of a fuel gas (not weight percent carbon of the total fuel gas), $100\% \times \text{g-H/g-HC}$

Note 1: Volume percent and mole percent are equivalent, but neither volume percent nor mole percent are equivalent to weight percent.

Note 2: **wt%H_{HC}** is equivalent to (defined by analogy) **wt%H_{2,HC}**. **part-inertgas** is equivalent to both (defined by analogy) **inertgas_{fuel}** and to **mol-inertgas**.

OUTPUT:

- SO₂concentration** on a dry basis for the combustion of a fuel gas

Note 3: Although **SO₂concentration** is on a dry basis, **mol-H₂O** is still an important dummy variable that needed to be calculated because **N_{2,H₂}** that accompanies **O_{2,H₂}** dilutes **SO₂concentration**.

INPUTS:

- H₂Sconcentration**
- vol%H₂O_{fuel}**
- vol%HC_{fuel}**
- vol%inertgas_{fuel}**
- MW_{HC}**
- wt%C_{HC}**
- wt%H_{HC}**
- vol% dryO_{2,exhaust}**

Note 4: The sum of the following four terms must total 100%: 1) **H₂Sconcentration** converted to a percent by dividing by 10,000 (i.e. **vol%H₂S_{fuel}** by analogy); 2) **vol%inertgas_{fuel}**; 3) **vol%HC_{fuel}**; and 4) **vol%H₂O_{fuel}**. **wt%C_{HC}** and **wt%H_{HC}** must total 100% by the definition of hydrocarbon. The sum of **wt%C_{HC}** and **wt%H_{HC}** must total 100%. For example, a fuel gas on a dry basis is 50-ppm H₂S, 2% CO₂, 3% N₂, and 95% methane: 1) **vol%H₂S_{fuel}** = 50 / 10,000 = 0.0%; 2) **vol%inertgas_{fuel}** = 2 + 3 = 5%; 3) **vol%HC_{fuel}** = 95%; 4) **vol%H₂O_{fuel}** = 0%; 5) **wt%C_{HC}** = 75%; and 6) **wt%H_{HC}** = 25%.

ASSUMPTIONS:

1. Any and all water in the fuel gas and/or in the ambient air is inert during combustion of the fuel gas.
2. All fuel gas consists of inert gas (e.g. N₂ and CO₂), gaseous hydrocarbons, hydrogen sulfide, and water vapor. Note 4 is the only reason why the water vapor in the fuel may not be negligible.
3. Ambient air— only O₂ and N₂—has 3.76 moles of N₂ per mole of O₂. Therefore, there are 4.76 moles of air per mole of O₂. Any and all water vapor in the ambient air is negligible because the output is on a dry basis and because of **assumption 1**.
4. The only source of O₂ for combustion is from the ambient air.
5. Perfect combustion is combustion that is complete and clean with no soot, PM, HC, VOC, CO, and NO_x in the exhaust gas. Therefore, **vol%_{dry}O_{2,exhaust}** must be greater than or equal to zero while all **part-inertgas**, all N₂, and all excess O₂ is inert in the combustion process.
6. For regulatory purposes (i.e. the purpose of developing this output), all of the sulfur in the fuel gas forms SO₂ in the exhaust gas and none of the sulfur is removed by from the exhaust gas.

Note 5: **Assumptions 1 – 5** are commonly accepted assumptions for combustion analysis. **Assumption 6** is based on 18 AAC 50.055(c), which states, “sulfur-compound emissions expressed as sulfur dioxide.”

SOLUTION:

Note 6: **Eqs. (1-1) – (1-6)** are definitions of variables as functions of inputs, constants, and other variables on a computational basis of 1 *gmole* hydrocarbon fuel gas (including hydrogen sulfide and inert gas).

$$\text{Eq. (1-1)} \quad \text{part-H}_2\text{S} = \text{H}_2\text{Sconcentration} / 10^6$$

$$\text{Eq. (1-2)} \quad \text{part-inertgas} = \text{vol\%}_{\text{dry}}\text{inertgas}_{\text{fuel}} / 100\%$$

$$\text{Eq. (1-3)} \quad \text{part-HC} = \text{vol\%}_{\text{dry}}\text{HC}_{\text{fuel}} / 100\%$$




$$\text{Eq. (1-4)} \quad \text{S}_{\text{fuel}} = \text{part-H}_2\text{S}$$

$$\text{Eq. (1-5)} \quad \text{C}_{\text{fuel}} = \text{part-HC} \times (\text{wt\%C}_{\text{HC}} / 100\%) \times (\text{MW}_{\text{HC}} / 12.01)$$

$$\text{Eq. (1-6)} \quad \text{H}_{2,\text{fuel}} = \text{part-H}_2\text{S} + (\text{part-HC} \times (\text{wt\%H}_{2,\text{HC}} / 100\%) \times (\text{MW}_{\text{HC}} / 2.016))$$



Note 7:

Eqs. (2-1) – (2-3) are the stoichiometric combustion equations for sulfur, carbon, and hydrogen, whereas the right arrows show exothermic chemical reactions. The inert water vapor from the fuel gas and from the ambient air was not shown in **eq. (2-3)**; see **assumptions 2 – 3**. **Eq. (2-4)** shows that the O_2 supplied by the ambient air minus the O_2 consumed in **eqs. (2-1) – (2-3)** is the O_2 in the exhaust gas. **Eq. (2-5)** shows that the N_2 supplied by the ambient air is the N_2 in the exhaust gas without any chemical change (e.g. zero NO_x from **assumption 4**). **Eq. (2-6)** shows that like the N_2 , the inert gas in the fuel is the same in the exhaust gas. The double arrows in **eqs. (2-4) – (2-6)** show no chemical reactions (i.e. inert from **assumption 5**).



Note 8:

Eqs. (3-1) – (3-3) are corollaries of **eqs. (2-1) – (2-3)**, respectively. **Eq. (3-4)** is a corollary of **eq. (2-4)** and of **eqs. (3-1) – (3-3)**. **Eq. (3-5)** is a corollary of **eq. (2-5)**, of **assumption 3**, and of **eq. (3-4)**.



Note 9:

Eq. (4-1) is the definition of $\text{vol}\%_{\text{dry}}O_{2,\text{exhaust}}$. **Eq. (4-2)** is the solution of **eq. (4-1)** as a function of mol-O_2 . **Eq. (4-3)** is the result of substituting mol-N_2 from **eq. (3-5)** into **eq. (4-2)**. **Eq. (4-4)** is the result of combining terms on the right side of **eq. (4-3)**. **Eq. (4-5)** is

the result of moving the **mol-O₂** term on the right side of **eq. (4-4)** to the left side and then factoring out **mol-O₂**. **Eq. (4-6)** is the result of multiplying both sides of **eq. (4-5)** by “100% - **vol% dryO_{2,exhaust}**.” **Eq. (4-7)** is the result of combining the two **vol% dryO_{2,exhaust}** terms on the left side of **eq. (4-6)** and isolating the **mol-O₂** term on the left side by division. **Eq. (4-8)** is the result of factoring out a constant in the denominator of **eq. (4-7)**.

$$\text{Eq. (4-1)} \quad \text{vol\% dryO}_{2,\text{exhaust}} = 100\% \times \text{mol-O}_2 / (\text{part-inertgas} + \text{mol-SO}_2 + \text{mol-CO}_2 + \text{mol-O}_2 + \text{mol-N}_2)$$

$$\text{Eq. (4-2)} \quad \text{mol-O}_2 = \text{vol\% dryO}_{2,\text{exhaust}} \times (\text{part-inertgas} + \text{mol-SO}_2 + \text{mol-CO}_2 + \text{mol-N}_2) / (100\% - \text{vol\% dryO}_{2,\text{exhaust}})$$

$$\text{Eq. (4-3)} \quad \text{mol-O}_2 = \text{vol\% dryO}_{2,\text{exhaust}} \times (\text{part-inertgas} + \text{mol-SO}_2 + \text{mol-CO}_2 + ((3.76 \times \text{mol-SO}_2) + (3.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O}) + (3.76 \times \text{mol-O}_2))) / (100\% - \text{vol\% dryO}_{2,\text{exhaust}})$$

$$\text{Eq. (4-4)} \quad \text{mol-O}_2 = \text{vol\% dryO}_{2,\text{exhaust}} \times (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O}) + (3.76 \times \text{mol-O}_2)) / (100\% - \text{vol\% dryO}_{2,\text{exhaust}})$$

$$\text{Eq. (4-5)} \quad \text{mol-O}_2 \times (1 - (3.76 \times \text{vol\% dryO}_{2,\text{exhaust}} / (100\% - \text{vol\% dryO}_{2,\text{exhaust}}))) = \text{vol\% dryO}_{2,\text{exhaust}} \times (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O})) / (100\% - \text{vol\% dryO}_{2,\text{exhaust}})$$

$$\text{Eq. (4-6)} \quad \text{mol-O}_2 \times ((100\% - \text{vol\% dryO}_{2,\text{exhaust}}) - (3.76 \times \text{vol\% dryO}_{2,\text{exhaust}})) = \text{vol\% dryO}_{2,\text{exhaust}} \times (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O}))$$

$$\text{Eq. (4-7)} \quad \text{mol-O}_2 = \text{vol\% dryO}_{2,\text{exhaust}} \times (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O})) / (100\% - (4.76 \times \text{vol\% dryO}_{2,\text{exhaust}}))$$

$$\text{Eq. (4-8)} \quad \text{mol-O}_2 = \text{vol\% dryO}_{2,\text{exhaust}} \times (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O})) / (4.76 \times (21\% - \text{vol\% dryO}_{2,\text{exhaust}}))$$

Note 10: **Eq. (5-1)** is the definition of **SO₂concentration**. **Eq. (5-2)** is the result of substituting **mol-N₂** from **eq. (3-5)** into **eq. (5-1)**. **Eq. (5-3)** is the result of combining terms on the right side of **eq. (5-2)**. **Eq. (5-4)** is the result of substituting **mol-O₂** from **eq. (4-8)** into **eq. (5-3)**. **Eq. (5-5)** is the result of combining terms in **eq. (5-4)**.

$$\text{Eq. (5-1)} \quad \text{SO}_2\text{concentration} = 10^6 \times \text{mol-SO}_2 / (\text{part-inertgas} + \text{mol-SO}_2 + \text{mol-CO}_2 + \text{mol-O}_2 + \text{mol-N}_2)$$

Eq. (5-2)
$$\text{SO}_2\text{concentration} = 10^6 \times \text{mol-SO}_2 / (\text{part-inertgas} + \text{mol-SO}_2 + \text{mol-CO}_2 + \text{mol-O}_2 + (3.76 \times \text{mol-SO}_2) + (3.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O}) + (3.76 \times \text{mol-O}_2))$$

Eq. (5-3)
$$\text{SO}_2\text{concentration} = 10^6 \times \text{mol-SO}_2 / (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O}) + (4.76 \times \text{mol-O}_2))$$

Eq. (5-4)
$$\text{SO}_2\text{concentration} = 10^6 \times \text{mol-SO}_2 / (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O}) + (\text{vol}\%_{\text{dry O}_2, \text{exhaust}} \times (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O}))) / (21\% - \text{vol}\%_{\text{dry O}_2, \text{exhaust}}))$$

Eq. (5-5)
$$\text{SO}_2\text{concentration} = 10^6 \times \text{mol-SO}_2 / ((1 + (\text{vol}\%_{\text{dry O}_2, \text{exhaust}} / (21\% - \text{vol}\%_{\text{dry O}_2, \text{exhaust}}))) \times (\text{part-inertgas} + (4.76 \times \text{mol-SO}_2) + (4.76 \times \text{mol-CO}_2) + (1.88 \times \text{mol-H}_2\text{O})))$$

Note 11: **Eqs. (6-1) – (6-4)** were derived such that the **eq. (6-4)** depends on only constants and inputs. **Eq. (6-1)** is the result of substituting **mol-SO₂**, **mol-CO₂**, and **mol-H₂O** from **eq. (5-5)** into **eqs. (3-1) – (3-3)** and then substituting **S_{fuel}**, **C_{fuel}**, and **H_{2, fuel}** into **eqs. (1-4) – (1-6)**. **Eq. (6-2)** is the result of combining the two **part-H₂S** terms in the denominator and combining the two **part-HC** terms in **eq. (6-1)**. **Eq. (6-3)** is the result of combining the two **MW_{CH}** terms, moving **part-inertgas**, and combining some constants in **eq. (6-2)**. **Eq. (6-4)** is the result of substituting **part-H₂S**, **part-inertgas**, and **part-HC** from **eq. (6-3)** into **eqs. (1-1) – (1-3)**, respectively.

Eq. (6-1)
$$\text{SO}_2\text{concentration} = 10^6 \times \text{part-H}_2\text{S} / ((1 + (\text{vol}\%_{\text{dry O}_2, \text{exhaust}} / (21\% - \text{vol}\%_{\text{dry O}_2, \text{exhaust}}))) \times (\text{part-inertgas} + (4.76 \times \text{part-H}_2\text{S}) + (4.76 \times \text{part-HC} \times (\text{wt}\%_{\text{C}_{\text{HC}}} / 100\%) \times (\text{MW}_{\text{HC}} / 12.01)) + (1.88 \times (\text{part-H}_2\text{S} + (\text{part-HC} \times (\text{wt}\%_{\text{H}_{\text{HC}}} / 100\%) \times (\text{MW}_{\text{HC}} / 2.016))))))$$

Eq. (6-2)
$$\text{SO}_2\text{concentration} = 10^6 \times \text{part-H}_2\text{S} / ((1 + (\text{vol}\%_{\text{dry O}_2, \text{exhaust}} / (21\% - \text{vol}\%_{\text{dry O}_2, \text{exhaust}}))) \times (\text{part-inertgas} + (6.64 \times \text{part-H}_2\text{S}) + (\text{part-HC} \times ((4.76 \times (\text{wt}\%_{\text{C}_{\text{HC}}} / 100\%) \times (\text{MW}_{\text{HC}} / 12.01)) + (1.88 \times (\text{wt}\%_{\text{H}_2, \text{HC}} / 100\%) \times (\text{MW}_{\text{HC}} / 2.016))))))$$

Eq. (6-3)
$$\text{SO}_2\text{concentration} = 10^6 \times \text{part-H}_2\text{S} / ((1 + (\text{vol}\%_{\text{dry O}_2, \text{exhaust}} / (21\% - \text{vol}\%_{\text{dry O}_2, \text{exhaust}}))) \times ((6.64 \times \text{part-H}_2\text{S}) + \text{part-inertgas} + (\text{MW}_{\text{HC}} \times \text{part-HC} \times ((0.396 \times \text{wt}\%_{\text{C}_{\text{HC}}} / 100\%) + (0.933 \times \text{wt}\%_{\text{H}_{\text{HC}}} / 100\%))))$$

Eq. (6-4)
$$\text{SO}_2\text{concentration} = \text{H}_2\text{Sconcentration} / ((1 + (\text{vol}\%_{\text{dry O}_2, \text{exhaust}} / (21\% - \text{vol}\%_{\text{dry O}_2, \text{exhaust}}))) \times ((6.64 \times \text{H}_2\text{Sconcentration} / 10^6) +$$

$$(\text{vol}\%_{\text{dry}} \text{inertgas}_{\text{fuel}} / 100\%) + (\text{MW}_{\text{HC}} \times (\text{vol}\%_{\text{dry}} \text{HC}_{\text{fuel}} / 100\%) \times ((0.396 \times \text{wt}\%_{\text{C}_{\text{HC}}} / 100\%) + (0.933 \times \text{wt}\%_{\text{H}_{\text{HC}}} / 100\%))))$$

Note 12: **Eq. (6-4)** is relatively long and could confuse some people needing to use this equation. To resolve this potential problem, **eq. (6-4)** was simplified in the permit by breaking it into sixteen simple steps.